



WATERBOY

FAIR DINKUM SOLAR PUMPS



WATERBOY 4C12183000

4" Centrifugal Solar Pumping System

FEATURES

- Brushless DC motor
- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency

BENEFITS

- Lift up to 130m
- Flow rate up to 72,000 L/day
- Simple installation
- Maintenance-free
- High reliability & life expectancy

\$11,590+GST

Contact us for delivery rates

Bore part number: 4C12183000B
 Dam Floating part number: 4C12183000D
 Bore pump extra cabling: 6000B
 Dam pump extra cabling: 6000D

4C12183000

| TDH | L/MIN | L/DAY |
|-----|-------|--------|
| 10 | 200 | 72,000 |
| 20 | 183 | 65,880 |
| 30 | 170 | 61,200 |
| 40 | 158 | 56,880 |
| 50 | 140 | 50,400 |
| 60 | 125 | 45,000 |
| 70 | 111 | 39,960 |
| 80 | 100 | 36,000 |
| 90 | 83 | 29,880 |
| 100 | 65 | 23,400 |
| 110 | 50 | 18,000 |
| 120 | 33 | 11,880 |
| 130 | 16 | 5,760 |

SOLAR PUMP SYSTEM INCLUDES:



4CSS Pump, Motor, and Controller



Power, Low Water and SS Safety Cable
Bore \$16p/m / Dam \$12p/m



Heavy Duty Cyclone Rated Pole Mount Frame



8x430w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

ACCESSORIES

- 6101 - Tank switch
- 6045NO - Pressure switch
- 6112 - 1.5" Double acting float valve
- 6015 - Sacrificial anode 1 1/4"



Tank full switch inc 20m cable \$165+GST



Pressure Switch 12 bar inc gauge & fittings \$275+GST



Double acting float valve For use with Pressure Switch - \$275+GST



Anode \$120+GST



Shipping Dimensions
1x Crate 440 x 60 x 65cm @ 280kg
1x Pallet 200 x 115 x 45cm @ 190kg